TECHNICAL SPECIFICATION

1. Scope:

1.1 Designations
IEC & GB: LR41 / LR736
JIS: LR41
ANSI: 192
OTHERS: AG3

1.2 Reference Document
IEC 60086-1 :2021 --- Primary Batteries - Part 1: General
IEC 60086-2 :2021--- Primary Batteries - Part 2: Physical and electrical specification
IEC 60086-5-2016- primary batteries –Part 5：Safety of batteries with aqueous electrolyte

2. Chemical System：

Alkaline-Manganese Dioxide (-) Zn | KOH | MnO2(+)
0% Mercurio (Hg) y 0% Cadmio (Cd).

3. Nominal Voltage：1.50 V

4. Average Weight：0.6 g

5. Nominal Capacity：

Designed for alkaline applications in compliance with IEC standards

6. Electrical characteristics：(Test condition: 20℃±2℃)

Items	Off-load voltage	(1kΩ) On-load voltage	Acceptance criteria
Initial (Within 30 days after delivery)	≥1.55V	≥1.50V	MIL-STD105E, Class Ⅱ, Double Sampling, AQL=0.4
After 12 months	≥1.52V	≥1.47V	

Acceptance criteria：

1) Test nine batteries
2) If the average discharge time is equal to or greater than the specified figure and no more than one battery has a service out of less than 80% of the specified figure, the batteries are considered to conform to standards.
3) One re-test is allowed to confirm the previous result.

7. *Safety characteristics*

Test item	Condition	Period	Requirements	Acceptance standard
High temperature and humidity test	57℃ 95%RH	10 d 18hrs/d	No leakage	**N=20, S1：Ac=2,Re=3**
External short circuit	Temp.: (20±5)℃	24 h	There shall be no explosion during this test	**N=9, Ac=0, Re=1**
Over-discharge Characteristics	Temp: 20±2℃; Load：68KΩ	Continuous discharge 48 hours after discharge termination	No leakage or explosion by eye	**N=9, Ac=0, Re=1**

8. Marking

The following markings will be stamped on the cathode can of the battery:

a) Designation：LR41
b) Polarity marking：“+”

c) Manufacturer trademark: Powercell
d) Mercury-free marking：0.0%Hg


9. Safety precautions：

a) Do not charge the battery as this may cause battery leakage and damage to charging equipment;
b) Insert batteries correctly with regard to the polarities (＋and－) marked on the battery and the equipment;
c) Do not short circuit, heat, or put the battery into fire;
d) Do not disassemble the battery as the internal electrolyte will corrode the skin
e) Do not use both new and used batteries at the same time
f) Please remove the depleted battery from the appliance to avoid leakage caused by over discharge;
g) Batteries should be kept out of reach of children to prevent accidental ingestion;
h) Before installing the battery into the electrical appliance, wipe the cover with alcohol to better utilize and protect the appliance;
i) Batteries should not come into contact with corrosive substances such as strong acids and alkalis.


10. Warranty period

3 years

11. Size and structure



Item	Size
A	7.7--7.9mm
B	3.3--3.6mm



Powercell Peru
Imported and distributed by Comercial y Distribuciones Sagitario SAC | RUC 20600218311
Canales oficiales Web: www.powercell.pe | Email: ventas@powercell.pe

This document constitutes the official technical specification of the product. Powercell reserves the right to modify parameters and tolerances herein without prior notice for continuous engineering improvement. All rights reserved.