TECHNICAL SPECIFICATION

1. Scope:

1.1 Designations
IEC & GB: LR6
JIS: AM-3
ANSI: AA
1.2 Reference Document
IEC 60086-1 :2021 --- Primary Batteries - Part 1: General
IEC 60086-2 :2021--- Primary Batteries - Part 2: Physical and electrical specification
1.3 Execution Standard:
GB/T 8897.2-2021

2. Chemical System:

Zinc/Potassium Hydroxide/Electrolytic Manganese Dioxide
0% Mercurio (Hg) y 0% Cadmio (Cd).

3. Nominal Voltage: 1.5 V

4. Average Weight: 23.0 g

5. Nominal Capacity:

Designed for alkaline applications in compliance with IEC standards

6. Electrical performance: (Test condition: Load resistance (±0.5%) 3.9Ω, test time: 0.3 seconds, temperature: 20±2℃)

	Open Circuit Voltage (V)	On-Load Voltage (V)	Acceptance Level
Fresh battery (within 30 days of delivery)	≥1.58	≥1.40	MIL-STD105E, Ⅱ, AQL=0.4
Stored for 12 months at room temperature	≥1.56	≥1.35	

7. *Leakage Resistance Performance*

Item	Condition	Test Duration	Result	Acceptance Level
Over-discharge Test	Continuous discharge with 10Ω resistor at 20℃±2℃ and 55±20%RH	Continuous discharge for 48 hours	Deformation of the battery shall not exceed the upper limit of the dimensional specification and no leakage visible to the naked eye shall occur.	**N=9, Ac=1,Re=2**
High Temperature and High Humidity Test	60 ±2°C Relative Humidity 90±5% RH	35 days		**N=20, Ac=1,Re=2**

8. Safety Performance

Item	Condition	Test Duration	Requirement	Acceptance Level
Short Circuit Characteristics	Ambient Temperature: 20 ±5°C	24 Hours	During the test period, the battery shall not explode.	**N=5, Ac=0,Re=1**
Three against One Charge	4 batteries connected in series short circuit, one of which is connected in reverse.	24 Hours		**N=20, Ac=0,Re=1**

9. Marking

The contents of the label:
(1)Model: LR6
(2)Registered Trademark: POWERCELL
(3)Nominal Voltage: 1.5V
(4)Battery Poloidal: "+"and"-"
(5)Warning words: Install and use correctly. Do not recharge, disassemble, heat and short-circuit.

10. Precaution for use


(1) Alkaline zinc-manganese batteries are non-rechargeable. Charging the battery may cause risk of leakage and explosion.
(2) Please install the battery correctly according to the +/- polarity markings.
(3) Do not short-circuit, heat, dispose of in fire, or attempt to disassemble the battery.
(4) Do not over-discharge the battery, as this may cause battery leakage and damage electrical appliances.
(5) New and used batteries, or batteries of different types or brands, should not be used together. When replacing batteries, please make sure to use the same brand and replace all of them.
(6) Please replace exhausted batteries in time to prevent over-discharge. Otherwise, it may cause battery leakage and damage electrical appliances.
(7) Direct soldering on the battery is prohibited, as this may damage the battery.

11. Shelf Life

Under conditions of temperature 20±2°C and relative humidity 55±20%RH, the battery shelf life is 8 years

Under room temperature conditions, the battery shelf life is 5 years

12. Dimensions



MODEL / DIMENSIONS(mm)	LR6
A (Max)	50.5
B (Min)	49.5
C (Min)	7.0
F (Max)	5.5
G (Min)	1.0
ø (Max)	14.5
ø (Min)	13.7

Powercell Peru
Imported and distributed by Comercial y Distribuciones Sagitario SAC | RUC 20600218311
Canales oficiales Web: www.powercell.pe | Email: ventas@powercell.pe

This document constitutes the official technical specification of the product. Powercell reserves the right to modify parameters and tolerances herein without prior notice for continuous engineering improvement. All rights reserved.